

TECHNICAL DATA SHEET

TENNIS COURT PAINT

PRODUCT SCOPE

Tennis Court paint is a top quality acrylic paint. This has a degree of color fastness & resistance to abrasion as required under such conditions. It gives a completely flat finish & therefore the problem of glaze is eliminated. Tennis Court paint is used on tennis court.

TECHNICAL INFORMATION	
APPEARANCE	Liquid Paste
ODOUR	Emulsion
Pack Viscosity	128 -130 KU @ Stormier Viscometer @ 25 °C
Specific Gravity	1.30~1.46 (Depends upon color)
pH	8.0 ~ 9.0
Color	Assorted
Application Method	Brush/ Roller/ Spray
Number of Coats	02 ~ 03
Thinning Ratio	Tennis court paint : WATER (1:1) by Volume
Solvent / Cleaner	Water
Flammability	Not Applicable
Surface Dry Time	01-02 Hour
Recoating Time	03-04 Hours
Coverage	10 ~ 12 m ² / Liter / Coat (Depends on Surface Porosity)
Finish	Smooth Matt Finish

SURFACE PREPARATION

Surface must be free from dust, dirt, grease, oil, heavy shoot, chalk, mildew etc. Remove all Old, flaking, loose paint to avoid adhesion problem.

New Surface Preparation

- After Plastering, allow the surface to dry for minimum 12~15 weeks. Moisture contents must not exceed 15% in the plaster before application.
- After the wall is dry, apply one thin coat of BERGER Water base primer/ NU Prime Seal and allow to dry for at least 2 hours.
- Apply tennis court paint with Brush or Roller with recommended number of coats and recommended time intervals.

Old Surface Preparation

- Wire-brush the surface to remove flaking, loose Paint.
- Scuff with suitable emery paper.

- Dust of the powder with dry brush.
- Apply one thin coat of BERGER Water base primer/ BERGER NU Prime Seal and allow drying.
- Apply tennis court paint with Brush or Roller with recommended number of coats and recommended time intervals.

APPLICATION INFORMATION

- For best results, apply 3 ~ 4 coats (Depends on surface porosity) of tennis coat paint with recommended time intervals.
- Dilute the product with 01: 01 ratio by volume with water for application. Do not apply "Thick Coats" to avoid Brush Marks.

SAFETY AND HANDLING PRECAUTIONS

- Use protective equipment while application e.g. Apron, Gloves, Protective Glasses and Dust Mask.
- Ensure adequate ventilation during application.
- In case of Eye Splashes, wash with plenty of Fresh Water and consult medical advice.
- In case of skin contact, wash with plenty of water. In case of skin irritation (Sensitive Skin), obtain medical advice.
- In case of ingestion, do not induce vomiting. Drink plenty of Milk/Water and immediately consult a physician.
- Store the product below 40 °C and avoid direct sunlight for a longer period.
- As long as the container is firmly sealed, the material can be kept for 18-Months without deterioration.