

## BERGER EPOXY THINNER

### PRODUCT SCOPE

Berger Epoxy Thinner is a unique blend of Aromatic as well as Aliphatic solvents, suitable for use in Berger Epoxy Products.

### TECHNICAL INFORMATION

Type of Product	Thinner
Specific Gravity	0.82~0.86
Grind	Clear
Flash Point	>10 °C
Color	Water White

### USAGE

- Epilux 218
- Epilux 78
- Epilux 300
- Epilux 4
- Other Epoxy products

### STORAGE AND HANDLING PRECAUTIONS

- Keep away from heat and spark sources.
- Keep under shed, away from direct sunlight.
- Keep the containers closed in storage.
- Never breath the dust, mist, gas, vapors from the container.
- Use the thinner in ventilation.
- Store below 30 °C to avoid the chances of explosion of containers due to vapor pressure.

### SAFETY AND PRECAUTIONS

- Avoid prolonged and repeated contact with skin.
- Avoid prolonged inhalation.
- Never try to ingest the product.
- Always use safety items, goggles, mask, gloves, apron for personal safety.
- Do not use the product in congested or poor ventilated areas.

## FIRST AID

### In Case of Eye Splashes

- Wash with plenty of flowing cold water.
- Immediately consult the physician.

### In Case of Inhalation (If the person feels dizziness or unconsciousness)

- Remove the person to open fresh air area.
- Provide artificial breathing if needed.
- Consult a doctor.

### In Case of Ingestion

- Drink plenty of water or milk.
- Do not induce vomiting.
- Consult a doctor.

### In Case of Skin Contact (If Irritation is felt)

- Wash with plenty of water and soap.
- Consult a doctor if irritation continues.

## SPILLAGE HANDLING

- Do not wipe the place with solvent.
- Use wood sawdust and sand and thoroughly spread on the spilled paint.
- Gather the mixture, store in some waste drum and dispose off according to local environment regulations.
- Never throw out the paint in open garbage areas where fire is a norm.